



### MODEL FP-6/7



#### DESCRIPTION

A durable foot pedal throttle assembly for use with Curtis electronic motor speed controllers.

#### APPLICATION

Curtis FP-6/7 Foot pedal assembly is ideal for use in electric forklifts, golf carts, electric street vehicles and other vehicle types.

#### FEATURES

- Rugged LM24 aluminium casing - ideal for tough environments such as material handling
- The entire foot pedal rotates on its mounting base - for maximum installation flexibility
- Cable exit points at rear - for easy installation
- Special return spring design ensures increased reliability
- 5K Curtis potentiometer
- Includes two adjustable microswitches
- The foot pedal arm can be mounted on either side of the mounting base
- Custom specific pedal arms possible

#### SPECIFICATIONS

- Maximum current for microswitches: 4A at 30V DC (Resistive load)
- 3 Wire 5K potentiometer (Curtis 98191)
- 7 Core cable. Length 1000mm
- Pedal shaft stainless steel SS 410


**CURTIS INSTRUMENTS, INC.**  
200 KISCO AVENUE  
MT. KISCO, NY 10549 USA  
TEL (914) 666-2971  
FAX (914) 666-2188

**CURTIS INSTRUMENTS, (UK) LTD.**  
5 UPPER PRIORY STREET  
NORTHAMPTON NN1 2PT, ENGLAND  
TEL 44 (0) 1604-629755  
FAX 44 (0) 1604-629876

**CURTIS INSTRUMENTS INDIA  
PRIVATE LTD.**  
1199, GHOLE ROAD  
PUNE 411004, INDIA  
TEL 91 (0) 20-5531288  
FAX 91 (0) 20-5539192

# MODEL FP-6/FP7

## DIMENSIONS mm



## INSTALLATION

Potentiometer – 0.5K Curtis Potentiometer P/N 98191

Wiring:

Wire Color	Function
Black	Potentiometer low
White	Potentiometer wiper
Red	Potentiometer high
Green	Footswitch 1
Blue	
Yellow	
Grey	Footswitch 2

Mounting: 2 x M8 Screws

## MODEL REFERENCE

FP-6 0 to 5K operation ( Black and white wire connection)

FP-7 5K to 0 operation ( Red and white wire connection )

**WARRANTY** Two year limited warranty from time of delivery.



is a trademark of Curtis Instruments, Inc.

Specifications subject to change without notice.

©Curtis Instruments, Inc. 2005

50120 REV A 10/05